

### WIZARD

### FOR MIXING, DRAINING, MOVING AND STORING DRUMS

The original MECO OMAHA Wizard is the most versatile unit of its kind. Telescoping oak handles provide necessary leverage for easy loading when extended. Handles retract into channel frame for storage. Double welded construction. Unique button rollers attached to barrel cradles allow drum to be rotated for draining or mixing while in a horizontal position. The Wizard handles 15, 30 and 55 gallon drums weighing up to 1000 lbs. Drums must be a minimum of 29" high for the chime hook to engage the drum. The Wizard is available set up or knocked down. Knocked down models ship in a carton via UPS. All units are  $18^1/2^*$  wide; orange enamel finish.

**Loading Procedure:** Place Wizard toes against bottom chime with hook over top chime. Extend handles to full length. Place foot on lower axle and pull back on handles; toes will automatically slide under the drum. Move foot to upper axle and continue pulling back until all four wheels are on the floor. Retract handles and hook for storage.

### • SET UP MODELS • 1,000 LB CAPACITY

MODEL NO.		FRAME	DRAIN	LEN		
	WHEELS	HEIGHT	HEIGHT	Handles Ext.	Handles Ret.	WEIGHT
W12R	5" Solid Rubber	221/2"	201/2"	64"	431/2"	52 lbs
W12SS	4" Steel	22"	20"			53 lbs
W12P	5" Polyolefin	221/2"	201/2"			48 lbs
W12H	Replacement Oak	Handle		1		3 lbs

### KNOCKED DOWN MODELS • 1000 LB CAPACITY

MODEL No.		FRAME DR		DRAIN LENGTH		707111111
	WHEELS	HEIGHT	HEIGHT	Handles Ext.	Handles Ret.	WEIGHT
W12R-KD	5" Solid Rubber	221/2"	201/2"	occorr.	2.500,000,000	55 lbs
W12SS-KD	4" Steel	22"	20"	64"	431/2"	56 lbs
W12P-KD	5" Polyolefin	221/2"	201/2"			56 lbs





### **ROCK-IT**

### BARREL LIFT AND DRUM STAND

The most economical drum stand for draining and storing 30 gallon and 55 gallon drums. One worker can load the double welded Rock-It with safety and ease. The exclusive MECO OMAHA skid-resistor frame eliminates the possibility of the unit sliding away while loading, making this one of the safest units of its kind. The chime hook formed into the nose plate hooks over the barrel chime eliminating the danger of the barrel sliding off during loading. The DS1, not equipped with wheels, is ideal for inexpensive permanent storage. DS2, DSR and DSP models have two rear swivel casters and two front load wheels. Options include a handle to increase leverage while tipping the load and a slide-out drip pan to protect your floor from spills and drips. The 12" x 12" steel pan accepts most absorbent pads. Drums must be a minimum of 29" high for the handle hook to engage the drum chime. The Rock-It handles drums weighing up to 1000 lbs. All models ship set up via UPS; orange enamel finish.

### • 1,000 LB CAPACITY

MODEL No.	LOAD WHEELS	SWIVEL CASTERS	LENGTH	WIDTH	HEIGHT	DRAIN HEIGHT	WEIGHT
		Models Wit	hout Hand	dle	· ·		200
DS1	None	None		18"	201/4"	183/4"	30 lbs
DS2	2 - 4" Steel	2 - 21/2" Steel	30"	30" 22"	22"	201/4"	39 lbs
DSR	2 - 5" Rubber	0 01 D-1-1-6-			221/2"	203/4"	37 lbs
DSP	2 - 5" Polyolefin	2 - 3" Polyolefin	•				34 lbs
	Mo	odels With Zinc El	ectro-Pla	ted Han	dle		
DS1-H	None	None	- 8	18"	201/4"	183/4"	35 lbs
DS2-H	2 - 4" Steel	2 - 21/2" Steel	201/-11	22"	22"	201/4"	44 lbs
DSR-H	2 - 5" Rubber	0 01 D-1-1-6-	361/2"		221/2"	203/4"	42 lbs
DSP-H	2 - 5" Polyolefin	2 - 3" Polyolefin					39 lbs
		Acce	ssories				252
DSH	Zinc plated repla	cement handle a	nd hook	- 36" lor	ıg		5 lbs
DSDP							9 lbs

ALL MODELS SHIP SET UP VIA UPS - HANDLE SHIPS IN SEPARATE BOX





**Loading Procedure:** Tilt drum and slide Rock-It nose under chime. Push drum back on stand and grasp top and bottom chime. Rock-It to horizontal position.





### DRAINER

### 4 WHEEL DRUM TRUCK FOR MOVING, STORING AND DISPENSING LIQUIDS

The Drainer is an original, exclusive MECO OMAHA design—don't settle for lookalikes. It facilitates moving and dispensing of liquids from a 55 gallon drum into a 5 gallon container. At the same time, it provides the convenience and ease of operation of a 4 wheel drum truck. Drain height is 14". All double welded construction and heavy duty mold-on rubber or steel wheels with roller bearings and grease fittings assure long life. The Drainer is also available with plain bore polyolefin wheels. Unique rollers on the frame allow drum rotation without removing from truck. The drum may be picked up from any side. The spigot can be rotated to the bottom from any position. Specially designed chime hook fits beneath spigot and does not interfere with dispensing operation. Use with drums between 30" and 40" in height. Unit is self-standing with the optional kickstand kit, select model number with "KS" suffix.

### • 1.000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
45VR	2 - 10" x 21/2" Mold-On Rubber			89 lbs
45VR-KS	2 - 6" x 2" Mold-On Rubber	62"	25"	91 lbs
45SS	2 - 10" x 21/2" Steel			93 lbs
45SS-KS	2 - 6" x 2" Steel			95 lbs
45P	2 - 10" x 21/4" Polyolefin 2 - 6" x 2" Polyolefin			61 lbs
45P-KS				65 lbs



### **TANDEM**

### HEAVY DUTY 4 WHEEL DRUM TRUCK

The Tandem is a heavy duty 4 wheel drum truck with full 1000 lb. capacity. The 1" diameter handle provides control and leverage and is double welded to the husky 11/4" diameter frame. The Tandem is available with mold-on rubber or steel wheels with grease fittings and roller bearings or plain bore polyolefin wheels. The replaceable chime hook assembly slides freely the full length of the hook shaft to accommodate fiber and steel drums 28" to 40" in height. Perfect balance permits easy breaking back over rear wheels; ideal for pallet loading and unloading. Truck stands upright both loaded and unloaded. An optional kickstand permits vertical out-of-the-way storage, select model number with "KS" suffix.

### 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
74VR	2 - 10" x 21/2" Mold-On Rubber			81 lbs
74VR-KS	2 - 6" x 2" Mold-On Rubber 2 - 10" x 21/2" Steel	62"	241/2"	83 lbs
74SS				90 lbs
74SS-KS	2 - 6" x 2" Steel			92 lbs
74P	2 - 10" x 21/4" Polyolefin 2 - 6" x 2" Polyolefin			58 lbs
74P-KS				60 lbs



### COMET

### THE FINEST SELF STANDING TWO HANDLE DRUM TRUCK

The Comet features a replaceable floating, spring loaded axle for ease in breaking back and will stand upright for convenient storage without a kickstand. Loads are perfectly balanced so the truck does the work—not the operator. The  $1^1/4^n$  diameter steel frame is double welded for strength. Replaceable chime hook assembly will accommodate both steel and fiber drums from  $24^n$  to  $42^n$  in height. The special beveled toes are replaceable. The  $10^n$  x  $2^1/2^n$  steel and mold-on rubber wheels have roller bearings and grease fittings. The Comet is also available with  $10^n$  plain bore polyolefin wheels.

### • 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
29VR	10" x 21/2" Mold-On Rubber	111		81 lbs
29SS	10" x 21/2" Steel	61"	23"	80 lbs
29P	10" x 21/4" Polyolefin			59 lbs



### HUSTLER

### FOR DRUM HANDLING FASE

The Hustler Drum Truck is engineered to eliminate problems normally associated with drum handling. For example: the Hustler is equipped with a unique chime hook assembly that will handle either steel or fiber drums from 25" to 48" in height—the entire hook assembly is replaceable. The drum cradle on the Hustler is designed to provide perfect balance while loading and moving. The drum is held securely in the cradle and in the curved bar attached to the chime hook assembly. Small roller wheels are placed behind the toes to facilitate loading and unloading from pallets. The Hustler is equipped with heavy duty 10" x 21/2" steel or mold-on rubber wheels with roller bearings and grease fittings for long life. Also available with 10" plain bore polyolefin wheels. The 11/4" diameter curved handle is welded to the 11/2" square tube stem for years of comfortable, dependable service. The Hustler is the finest standard model drum truck available.

# Hustler loading on and off pallets or skids 68VR HUSTLER

### 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
68VR	10" x 21/2" Mold-On Rubber		7	71 lbs
68SS	10" x 21/2" Steel	59"	241/2"	70 lbs
68P	10" x 21/4" Polyolefin			46 lbs

### CHALLENGER

### SELF-STANDING • STAYS OUT OF THE WAY UNTIL YOU NEED IT

The Challenger is perfectly balanced to stand upright and out of the way, thus saving floor space and preventing tripping accidents by keeping aisles and docks clear of trucks. The Challenger is equipped with a unique chime hook assembly that will handle either steel or fiber drums from 25" to 48" in height—the entire hook assembly is replaceable. The drum cradle on the Challenger is designed to provide perfect balance for loading and moving. The drum is held securely in the cradle and in the curved bar attached to the chime hook assembly. The Challenger is equipped with heavy duty 10" x 21/z" steel or mold-on rubber wheels with roller bearings and grease fittings for long life. Also available with 10" plain bore polyolefin wheels. The 11/4" diameter curved handle is securely welded to the 11/2" square tube stem.



### • 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
23VR	10" x 21/2" Mold-On Rubber			75 lbs
23SS	10" x 21/2" Steel	59" 241/2	241/2"	74 lbs
23P	10" x 21/4" Polyolefin			51 lbs

### **ECONOMY**

### FOR INEXPENSIVE DRUM HANDLING

No frills, but gets the job done. **MECO OMAHA**'s original design of this heavy duty drum truck keeps your costs down. Sliding chime hook adapts this truck for 30 and 55 gallon drums between 30" and 42" high. **MECO OMAHA**'s high quality manufacturing touch is visible in the Economy Truck's all double welded construction. All-steel wedge toes are beveled for easy loading and securely welded to the heavy 11/4" diameter steel frame. Available only with 10" x 21/4" plain bore polyolefin wheels. Optional kickstand permits the unit to stand straight up for storage, select model number with "KS" suffix. Can ship UPS for additional savings. You will not find a better drum truck for the money.

### • 1,000 LB CAPACITY • UPS SHIPPABLE WITH OVERSIZE CHARGE

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
62P	10" x 2¹/₄" Polyolefin	59"	251/2"	50 lbs
62P-KS	10 X 21/4 Polyoletin	29"		52 lbs





### **POLY DRUM TRUCK**

CHOOSE A UNIT FOR STANDARD POLY DRUMS OR OVERPACK DRUMS

The Poly Drum Truck features a double welded 11/4" diameter steel frame for years of wear. Breaking back drums is almost effortless with the replaceable floating, spring loaded axle.

Specially designed toe pads greatly minimize the chance of puncture when handling plastic or poly drums. Locking belt mechanism keeps drum safe and secure on the truck. Drum must be at least 29" in height for belt to engage. The Standard model is ideal for transporting all drums except overpacks; the Overpack model is equipped with a longer strap to handle large diameter drums such as overpacks and salvage drums.

The  $10" \times 2^{1/2}"$  steel and mold-on rubber wheels have roller bearings and grease fittings. Also available with 10" plain bore polyolefin wheels. Self standing for convenient storage.



### STANDARD MODEL • 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
29VR-1	10" x 21/2" Mold-On Rubber			83 lbs
29SS-1	10" x 21/2" Steel	61"	23"	82 lbs
29P-1	10" x 21/4" Polyolefin	900 Februar   1 100 Feb		60 lbs

### • OVERPACK MODEL • 1,000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
29VR-2	10" x 21/2" Mold-On Rubber			83 lbs
29SS-2	10" x 21/2" Steel	61"	23"	82 lbs
29P-2	10" x 21/4" Polyolefin			60 lbs

### TRUCKS FOR HANDLING POLY DRUMS

### POLY DRUM DRAINER TRUCK

HANDLES ALL TYPES OF DRUMS EXCEPT OVERPACKS

The Poly Drum Drainer Truck provides the convenience and ease of operation of a 4 wheel drum truck. Contents from a 55 gallon poly, fiber or metal drum can be transported and dispensed into a 5 gallon container. Drain height is 14". Chance of puncture to poly drums is minimized thanks to specially engineered toe pads. Easy-to-use safety belt system secures the drum to the truck.

Double welded steel frame for long life in an industrial environment. Mold-on rubber and steel wheels have roller bearings and grease fittings; polyolefin wheels have a plain bore.

Kickstand is included for upright storage. Not for use with overpacks.



45VR-KS-1
POLY DRUM DRAINER TRUCK

### • 1.000 LB CAPACITY

MODEL NO.	WHEELS	HEIGHT	WIDTH	WEIGHT
45VR-KS-1	2 - 10" x 21/2" Mold-On Rubber 2 - 6" x 2" Mold-On Rubber	62"		96 lbs
45SS-KS-1	2 - 10" x 21/2" Steel 2 - 6" x 2" Steel		25"	97 lbs
45P-KS-1	2 - 10" x 21/4" Polyolefin 2 - 6" x 2" Polyolefin			71 lbs



### LO-TRUCK

### CHOICE OF HINGED, RIGID OR 3-WAY HANDLES . MOVES OPEN DRUMS WITHOUT SPILLING

The MECO OMAHA Lo-Truck is ideal for moving open full barrels without spilling. Heavy duty mold-on rubber, steel or polyolefin wheels with a 3" swivel caster provide smooth movement and maximum maneuverability over all types of surfaces. Smooth rolling roller bearings assure long life and effortless transportation of otherwise troublesome cargo. Polyolefin wheels have a plain bore. Select a rigid handle (LT Model), hinged handle (HLT Model) or 3-way hinged handle (CLT Model). The low profile frame, with only 1/2" of underclearance, makes loading much easier than with other higher units. All models are 33" overall width with a 27" opening width. All welded construction for longer life. For use with 55 gallon drums only.

### · CLT MODELS SHIP IN A CARTON VIA UPS

MODEL NO.	RUNNING GEAR	CAPACITY	HEIGHT	WEIGHT
LT4	2 - 6" x 2" Mold-On Rubber Load Wheels		31"	35 lbs
CLT4	1 - 3" Polyolefin Swivel Caster	1,000 lbs	381/2"	37 lbs
HLT4	1 - 3 Tolydielli Towiver Caster		301/2	37 lbs
LT8	0. 0101.011113//1-	31"	40 lbs	
CLT8	2 - 6" x 2" Steel Load Wheels 1 - 3" Steel Swivel Caster	1,200 lbs	381/2"	42 lbs
HLT8	1 - 3 Steel Swiver Caster			42 lbs
LTP	0 0 0 0 0 0 0	1,200 ibs	31"	32 lbs
CLTP	2 - 6" x 2" Polyolefin Load Wheels 1 - 3" Polyolefin Swivel Caster		381/2"	34 lbs
HLTP	1 - 3 Folyolelli Swiver Caster		30'/2	34 lbs





### **OMAHA'S TOP ATTRACTIONS**







MANUFACTURING AMERICA'S FINEST MATERIAL HANDLING & STORAGE EQUIPMENT SINCE 1907

MODERN EQUIPMENT COMPANY, INC.










### DRUM LIFTER

### EASY TO USE WITH FORKLIFT OR HOOK

The Drum Lifter is designed for no-tilt lifting of open or closed head drums with or without tops in place. Our self adjusting Drum Lifter instantly adapts to individual drum loads with its unique compressing action. The heavier your drum, the tighter our lifter will grip. Simple enough for use by one person with any overhead lifting system. Opening for forklift tine or hook attachment is 21/2" x 5". For use with steel drums only.

### · SHIPS IN A CARTON VIA UPS

	MODEL NO.	CAPACITY	WEIGHT
81	DL1	3,000 lbs	45 lbs



### **DRUM SLING**

### SIMPLIFIES LIFTING HORIZONTAL DRUMS

Lift 55 gallon drums from the horizontal position with our MECO OMAHA Drum Sling. This simple and effective Drum Sling consists of two 181/2" legs of 1/2" steel round bar with a 1000 lb. capacity. The Drum Sling is strong enough for your heaviest drums. The 3" x 6" steel lifting ring is designed to handle hooks of all standard overhead lifting systems. Lifting ring also accommodates 4" forklift tines. For use with steel drums only.

### SHIPS IN A CARTON VIA UPS

MODEL NO.	CAPACITY	WEIGHT
SL1	1,000 lbs	8 lbs





Easy to Tilt Drums With Forklift

### DRUM CADDY

### FOR DRUM HANDLING EASE WITH FORKLIFT

MECO OMAHA Drum Caddies allow you to transport drums with your forklift. This simple and inexpensive piece of equipment is designed for safety. The manual handling of drums is greatly reduced. Steel band slips over your drum and is fastened with a specially designed overcenter latch. Unique 5" x 3" pivoting fork stirrups will allow you to tilt your drums for ease of dispensing. For use with steel drums only.

### · SHIPS IN A CARTON VIA UPS

MODEL NO.	DRUM SIZE	CAPACITY	WEIGHT
DC30	30 Gallon 18"-181/2" diameter	1.000 lbs	14 lbs
DC55	55 Gallon 22"-221/2" diameter	1,000 lbs	15 lbs



### **ROUND DRUM DOLLIES**

FOR 30 OR 55 GALLON DRUMS

MECO OMAHA Drum Dollies save time, money and effort by making your drums mobile. Four heavy duty swivel casters allow drums to turn 360 degrees for maximum maneuverability—casters are welded to frame for greater strength. Choice of 2½" or 3" polyolefin or steel wheels. Designed for optimum stability with casters inside frame to prevent breaking. Outside ring extends above cross frame so that drum sets into dolly, thus preventing container from slipping. The drum is 4" off floor with 3" casters; 3³/4" off floor with 2½" casters. This dolly can be used to transport full drums or make empty drums mobile. Ideal for converting empty drums into mobile refuse containers.

### · SHIPS IN A CARTON VIA UPS

MODEL No.	DRUM SIZE	I.D.	SWIVEL CASTERS	HEIGHT	CAPACITY	WEIGHT
433R		8	3" Polyolefin	51/2"	900 lbs	18 lbs
4338	30 Gallon	101/4"	3" Steel	31/2	1,200 lbs	21 lbs
434R			21/2" Polyolefin	51/4"	600 lbs	17 lbs
4348			21/2" Steel		900 lbs	20 lbs
435R	6	8	21/2" Polyolefin	31/4	600 lbs	21 lbs
435S	55	231/4"	21/2" Steel		900 lbs	22 lbs
436R	Gallon	lon 231/4"	3" Polyolefin	51/2"	900 lbs	21 lbs
436S			3" Steel		1,200 lbs	24 lbs



### OVERPACK DRUM DOLLIES

FOR LOW COST TRANSPORT OF OVERPACK AND SALVAGE DRUMS

The MECO OMAHA Overpack Drum Dolly safely contains a wide variety of steel and poly drums within a 21/2" deep ring. Drum is only 4" off floor for maximum stability. Four 3" swivel casters ensure complete maneuverability—choice of polyolefin or steel wheels. Orange enamel finish; 27" inside diameter.



### • SHIPS IN A CARTON VIA UPS

MODEL NO.	SWIVEL CASTERS	HEIGHT	CAPACITY	WEIGHT	
437P	3" Polyolefin	51/2"	900 lbs	23 lbs	
437S	3" Steel	3.72	1,200 lbs	26 lbs	

### **DOUBLE DRUM DOLLIES**

### MOVE TWO 30 OR 55 GALLON DRUMS AT A TIME - DOUBLE YOUR EFFICIENCY

The Double Drum Dolly from **MECO OMAHA** enables a worker to move two drums at a time instead of one—productivity is increased! Drums are contained safely and securely within a 21/2" deep ring. Four 3" steel cross strips support the load; a 21/2" wide lengthwise strip with a steel angle stiffener increases rigidity and reduces flex under load. Drum is only 51/4" off floor. Six double ball race swivel casters provide 1800 lbs. capacity and ensure total maneuverability. Orange enamel finish.

## 872P DOUBLE DRUM DOLLY

### · SHIPS IN A CARTON VIA UPS

MODEL NO.	DRUM SIZE	DIMENSIONS L x W x H	SWIVEL CASTERS	CAPACITY	WEIGHT	
866P	30 Gallon	40" x 191/2" x 63/4"	41 D-1-1-6-	4 000 !!	37 lbs	
872P	55 Gallon	48" x 231/2" x 63/4"	4" Polyolefin	1,800 lbs	43 lbs	







### SOLID DECK DRUM DOLLIES

- · Solid deck provides great overall support
- · Deck with lip retains the load
- · Four heavy duty swivel casters for maximum maneuverability
- · Casters welded to the frame for great strength
- Drum is 35/8" off floor with 21/2" casters
- · Drum is 37/8" off floor with 3" casters
- · Orange enamel finish



### · SHIPS IN A CARTON VIA UPS - HANDLE SHIPS IN SEPARATE BOX

MODEL NO.	DRUM SIZE	I.D.	SWIVEL CASTERS	HEIGHT	CAPACITY	WEIGHT
SDD5P	5 gal.	121/8"	2½" Polyolefin	61/8"	600 lbs	22 lbs
SDD55R	55 gal.	231/4"	3" Hard Rubber	53/8"	900 lbs	30 lbs
SDD55S	55 gal.	231/4"	3" Steel	53/8"	900 lbs	36 lbs
SDD85P	85 gal.	287/8"	3" Polyolefin	53/8"	900 lbs	38 lbs

### MODELS WITH ZINC ELECTRO-PLATED HANDLE

MODEL NO.	DRUM SIZE	I.D.	SWIVEL CASTERS	HEIGHT	CAPACITY	WEIGHT
SDD55R-H	55 gal.	231/4"	3" Hard Rubber	53/8"	900 lbs	30 lbs
SDD55S-H	55 gal.	231/4"	3" Hard Steel	53/8"	900 lbs	34 lbs

MODEL NO.	DESCRIPTION	DIMENSIONS	COATING	WEIGHT
DTH	Replacement Handle	3/8" x 36" L	Zinc Plated	2 lbs



### HEAVY DUTY DRUM DOLLY TRANSPORTS LOADS UP TO 2000 LBS.

- · All welded steel construction
- 25<sup>1</sup>/<sub>4</sub>" diameter x 7<sup>1</sup>/<sub>8</sub>" height overall
- · Orange enamel finish
- · Fits drum capacity 55 gallon
- 23<sup>1</sup>/<sub>4</sub>" inside diameter
- · Swivel caster includes brake
- Drum is 55/8" off floor

### · SHIPS IN A CARTON VIA UPS

93	MODEL NO.	DRUM SIZE	SWIVEL CASTERS	HEIGHT	LENGTH	CAPACITY	WEIGHT
	HDD-55PHL	55 gal.	4" Phenolic	71/8"	251/4"	2,000 lbs	35 lbs



### 8-WHEEL DRUM DOLLY

HAS A UNIQUE DESIGN FEATURING EIGHT CASTERS TO SMOOTHLY TRANSPORT YOUR LOAD

- · All welded steel construction
- · 267/8" diameter x 7" height overall
- Orange enamel finish
- Fits drum capacity 55 gallon
- 24" inside diameter
- Drum is 51/8" off floor

### SHIPS IN A CARTON VIA UPS

MODEL NO.	DRUM SIZE	SWIVEL CASTERS	HEIGHT	LENGTH	CAPACITY	WEIGHT
836S	55 gal.	4" Steel	7"	267/8"	2,000 lbs	29 lbs



SWIVEL CASTERS

3" Polyolefin

HEIGHT

CAPACITY

900 lbs

WEIGHT

24 lbs

### OUTRIGGER DRUM DOLLY

### SAVE TIME, MONEY AND EFFORT BY MAKING DRUMS MOBILE

- · Protective steel outriggers over each caster
- · Double welded steel frame with a 21/2" deep lip
- · Four heavy duty swivel casters permit 360 degree maneuverability

536-RG OUTRIGGER DRUM DOLLY

- · Casters are welded to the frame for greater strength
- · Orange enamel finish
- Drum is 37/8" off floor





SHIPS IN A CARTON VIA UPS

536-RG

MODEL NO. DRUM SIZE I.D.

55 gal. 231/4"



a promised shipping date!



**CALL TODAY FOR YOUR PROMISED DATE!** 800-228-7334



### TRIANGULAR DRUM DOLLY

LOW-PROFILE DESIGN MAKES LOADING AND UNLOADING SAFE AND EASY

- %" thick steel construction for years of industrial use
- · Drum safely rests 1" above the floor



### SHIPS IN A CARTON VIA UPS

MODEL NO.	DRUM SIZE	SWIVEL CASTERS	HEIGHT	CAPACITY	WEIGHT
T3P	55 gal.	3" Polyolefin	51/4"	700 lbs	26 lbs





### PORTABLE DRUM RACKS

MECO OMAHA RACKS SAVE SPACE AND MONEY • CHOICE OF ALL WELDED OR KNOCKED DOWN CONSTRUCTION

MECO OMAHA's all welded Portable Drum Racks allow use of forklift to move and store drums—saving time and manpower. Formed drum cradles of 1/4" steel bar, heavy wall rectangular steel tubing horizontal frame and square tubing cross supports combine to make these units almost indestructible. Individual drum racks may be shipped assembled ready for use or shipped knocked down via UPS. Racks stack four high. Two drum unit has 1600 lbs. capacity and a stacked capacity of 6400 lbs. Three drum unit has 2400 lbs. capacity and a stacked capacity of 9600 lbs. Two drum models have four-way forklift access; three drum models have two-way access, front and rear. Center to center of drum cradles is 26".

### · SET UP MODELS

MODEL NO.	HEIGHT	LENGTH	DEPTH	WEIGHT	
PDR2	401/-1	451/2"	201	40 lbs	
PDR3	121/2"	711/2"	30"	75 lbs	

\* KNOCKED DOWN MODELS \* SHIP IN A CARTON VIA UPS\*


MODEL NO.	HEIGHT	LENGTH	DEPTH	WEIGHT
PDR2-KD	401/-11	451/2"	201	48 lbs
PDR3-KD	121/2"	711/2"	30"	72 lbs

<sup>\*</sup>PDR3-KD SHIPS IN TWO CARTONS





All welded PDR2 is identical except for bolts



**NOTE:** Due to increased length of the three drum models, it is recommended that they not be moved stacked more than two racks high. Movement of more than two racks high could create an unbalanced condition.

### MODULAR DRUM STORAGE RACKS

FLEXIBLE SYSTEM - NO TOOLS OR HARDWARE REQUIRED - DISPENSE FROM LOWER LEVEL - STACK 5 HIGH

Each of the four **MECO OMAHA** Modular Drum Storage Racks can be used individually or can be easily stacked up to five levels high by using connector posts. No tools or fasteners are needed. Constructed of heavy duty, all double welded steel for durability. Designed for convenient forklift entry front and rear. Drums can be removed or replaced without disturbing other drums in the racks. Height from floor to top of first level is 7½ when used without socket feet or connector posts.

Draining liquid from drums on the lower level is easy. Simply use the MDRF2 socket feet to raise each rack so the lower level is 16" high for draining into a 5 gallon pail.

### • HIGH VISIBILITY ORANGE ENAMEL FINISH


MODEL No.	NO. OF Drums	HEIGHT	WIDTH	DEPTH	CAPACITY PER LEVEL	WEIGHT
MDR1	1		35"	36"	1,500 lbs	31 lbs
MDR2W	2	121/2"	61"		2,000 lbs	52 lbs
MDR2D			35"	72"		66 lbs
MDR4	4		61"		2,800 lbs	122 lbs
MDRP (Set of 4)		30"		ŝ)	AZ.	19 lbs
MDRF1 (Set of 4)		41/2"				5 lbs
MDRF2 (Set of 4)		131/2"				11 lbs





### MDRF

Socket feet have 3" square floor plates for use on resilient or uneven floors or when stacking more than 3 levels high. 41/2" in height.



**MDRF2** Socket feet attach easily, have 3"square floor plates and are 131/2" in height. No tools or fasteners needed to add feet or posts to Modular Drum Storage Racks.





### DR3 DR4 4 DRUM RACK

### **DRUM STORAGE RACKS**

PERMANENT STORAGE RACKS SHIPPED KNOCKED DOWN WITH COMPLETE INSTRUCTIONS FOR EASY ASSEMBLY

**MECO OMAHA** Drum Storage Racks are constructed of heavy duty steel angle. They are engineered for orderly handling, selective storage and removal of 30 and 55 gallon drums. Assembly is easy—simply bolt four vertical legs to individual levels, attach X-bracing to ends and rack is ready to accept drums. For maximum flexibility in drum storage, racks may be ordered to permit back to back installation allowing the user to customize every system to his own requirement. By combining units, any degree of capacity in nearly any type of space can be obtained. Designed for convenient forklift entry front and rear; all units are 34" deep.



### SHIPS KNOCKED DOWN IN A CARTON

MODEL NO.	NO. OF LEVELS	HEIGHT TO TOP OF FIRST LEVEL	HEIGHT	WIDTH	CAPACITY	WEIGHT
DR3	3	81/2"	70"	33"	2,400 lbs	159 lbs
DR4	2	18"	481/2"	60"	3,200 lbs	158 lbs
DR6-2H				851/2"	4 000 lb-	208 lbs
DR6-3H	3	81/2"	70"	60"	4,800 lbs	226 lbs
DR9	3	0./2	70	851/2"	7,200 lbs	308 lbs

### LET MECO OMAHA SOLVE YOUR DRUM STORAGE PROBLEMS





### DRUM PALLET RACKS

HEAVY DUTY • VERSATILE RACK FOR DRUM OR PALLET STORAGE

Satisfy your high capacity drum storage requirements with the **MECO OMAHA** Drum Pallet Rack. Designed to store 30 and 55 gallon drums; accepts 12 or 16 drums depending upon model. Each level has a capacity of 4825 lbs.

Rack is easy to assemble by bolting the load beams to the all welded 3" structural channel upright frame—no special tools required. Frames are punched full height on 4" centers permitting 2" vertical adjustability of beams.

The portable drum cradles are made of 11/4" diameter tubing to prevent premature drum wear and can be positioned on the load beams to meet user requirements. Cradles are included with the rack. Drum cradles can be removed from any level to allow storage of palletized material.

Add-on units of one upright frame, load beams and cradles can be ordered. Additional cradles can be ordered separately.

Gray enamel finish.

### • SHIPS KNOCKED DOWN • ALL UNITS 36" DEEP

MODEL NO.	TYPE	DESCRIPTION	HEIGHT	WIDTH	CAPACITY	WEIGHT
DPR12	3 Level	Starter	84"	105"	14,475 lbs	477 lbs
DPR12-A	12 Drum	Add-On		102"		413 lbs
DPR16	4 Level	Starter	120"	105"	19,300 lbs	651 lbs
DPR16-A	16 Drum	Add-On		102"		558 lbs
DPRC		Drum Cradle		12"	800 lbs	9 lbs